MegaMile®

QUICK REFERENCE TREAD GUIDE

Product Availability (Tread Depth in Shaded Boxes)

ALL POSITION RETREADS

Tread Size - mm	195	205	210	215	220	230	240	245	270	280	310	360
Tread Size - standard	7	8	8.5N	8.5	9	9.5	10.5	11	14	15	16	18
Global			15		15	15						
Global Siped			15									
Highway LP		18		18								
Spread Axle	18	18	18		18		20					
Waste Hauler Rib		24		24		24	24	26	26	26		
Wide Base Rib										16	16	16

DRIVE RETREADS

Tread Size - mm	180	195	205	210	215	220	230	235	240	245	250	255	270	280	290	330	360	360
Tread Size - standard	6	7	8	8.5N	8.5	9	9.5	10	10.5	11	12	12.5	14	14.5	15	17	18	18D
ATD				25		25	25		25		25(1)							
Deep Drive		22	22		22	22												
Drive Master	22	22	22			22												
HCM			28			28		28			28(2)							
HWT		26	26			26												
MM Traction			26			26	26		26									
Power Trac			24		24		24											
PTT		22	22		22	22	22		22									
TA222			20		20	20												
Ultra Grip		22	22			22												
Wide Base Lug															26	26	26	26
Wide Base Lug Deep																		30
Z Trak			26			26			26	32		32	32	32				

TRAILER RETREADS

Tread Size - mm	180	205	210	215	220	230	240
Tread Size - standard	6	8	8.5N	8.5	9	9.5	10.5
Highway LP (Shallow)	12	14		14	14		
Trailway		12	12		12	12	12

(1) Recommended for speeds less than 65 mph.
(2) Used in intermittent highway service with maximum speed of 50 mph and not to exceed a distance traveled of 50 miles in any 1½ hour period.

To learn more please contact your Oliver Sales Representative or visit

www.megamileretreads.com

Oliver Rubber Company, One Parkway South, Greenville, SC 29602-9001, 1-866-464-2580

An Equal Opportunity Employer.
Copyright © 2023 Oliver Rubber Company All rights reserved. (03/23)
MegaMile® retreads are subject to a continuous development program. Oliver Rubber Company reserves the right to change product specifications at any time without notice or obligations.