

BFGoodrich[®] ST244

Take control of the miles ahead with this long-lasting, even-wearing steer/all-position highway tire that's SmartWay® verified.

SmartWay®
Verified



GOES THE DISTANCE

» Seriously long-lasting tire



MAX FUEL EFFICIENCY

» Less stops at the pump



RETREADABILITY COMES STANDARD

» Multiple lives

5 **YEAR**
(3)

5 Year / 2-Retread Manufacturer's
Limited Casing Guarantee



| Application | Highway | Regional | Urban | Coach/ Bus | On/ Off-Road |
|-------------|---------|----------|-------------------------|---------------|------------------------|
| Position | Steer | Drive | Trailer | | |
| | | | Recommended Application | | Acceptable Application |

| Size | Load Range | Catalog Number | Tread Depth 32nds | Max. Speed (1) | | Loaded Radius | | Overall Diameter | | Overall Width (2) | | Approved Wheels (Measuring wheel listed first) | Min. Dual Spacing (2) | | Rev's Per Mile | Max. Load Per Tire Single | | | | Max. Load Per Tire Dual | | | |
|-------------|------------|----------------|----------------------|-------------------|-----|---------------|-----|------------------|------|----------------------|-----|---|-----------------------|-----|----------------|---------------------------|-----|------|-----|-------------------------|-----|------|-----|
| | | | | mph | kph | in. | mm. | in. | mm. | in. | mm. | | in. | mm. | | lbs. | psi | kg. | kPa | lbs. | psi | kg. | kPa |
| 11R22.5 | G | 40525 | 18 | 75 | 120 | 19.1 | 486 | 41.1 | 1043 | 10.5 | 267 | 8.25, 7.50 | 12.5 | 318 | 505 | 6175 | 105 | 2800 | 720 | 5840 | 105 | 2650 | 720 |
| 11R22.5 | H | 92401 | 18 | 75 | 120 | 19.2 | 487 | 41.1 | 1044 | 12.2 | 309 | 8.25, 7.50 | 12.5 | 318 | 505 | 6610 | 120 | 3000 | 830 | 6005 | 120 | 2725 | 830 |
| 275/80R22.5 | G | 61456 | 18 | 75 | 120 | 18.6 | 472 | 40.0 | 1016 | 10.9 | 277 | 8.25, 7.50 | 12.2 | 311 | 519 | 6175 | 110 | 2800 | 760 | 5675 | 110 | 2575 | 760 |
| 11R24.5 | H | 58109 | 18 | 75 | 120 | 20.2 | 513 | 43.3 | 1100 | 11.0 | 279 | 8.25, 7.50 | 12.5 | 318 | 478 | 7160 | 120 | 3250 | 830 | 6610 | 120 | 3000 | 830 |
| 275/80R24.5 | G | 77897 | 18 | 75 | 120 | 19.2 | 488 | 41.3 | 1049 | 10.6 | 269 | 8.25, 7.50 | 12.2 | 311 | 502 | 6175 | 110 | 2800 | 760 | 5675 | 110 | 2575 | 760 |

Note: Wheel listed first is the measuring wheel.

(1) Exceeding the lawful speed limit is neither recommended nor endorsed.

(2) Tire section widths and overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

(3) 5 Year / 2-Retread Limited Casing Guarantee when retreaded by an authorized Michelin Retread Technologies (MRT) Dealer or an Oliver Retread dealer.

See www.bfgoodrichtrucktires.com for more information.

BFGoodrich® tires are subject to a continuous development program. BFGoodrich® Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligation.

» Take control today at BFGoodrichTruckTires.com.

To Find Your Nearest BFGoodrich® Commercial Truck Tire Dealer Call:
United States 1-877-788-8899; Canada, 1-888-871-6666; Mexico, 011-52-442-296-1600
or visit www.bfgoodrichtrucktires.com
Copyright © 2024 MNA, Inc. All rights reserved. (12/24)

