

BFGoodrich DR444

Take control mile after mile with this long-lasting, rain-fighting highway and regional drive tire.



GOES THE DISTANCE

» Seriously long-lasting tires



SERIOUS GRIP

» Bring on the rain



RETREADABILITY COMES STANDARD

» Multiple lives

5 YEAR ⁽³⁾

5 Year / 2-Retread Manufacturer's
Limited Casing Guarantee



Application	Highway	Regional	Urban	Coach/ Bus	On/ Off-Road
Position	Steer	Drive	Trailer		

■ Recommended Application

Size	Load Range	Catalog Number	Tread Depth 32nds	Max. Speed (1) mph	Loaded Radius		Overall Diameter		Overall Width (2)		Approved Wheels (Measuring wheel listed first)	Min. Dual Spacing (2)		Revs Per Mile	Max. Load Per Tire Single				Max. Load Per Tire Dual			
					in.	mm.	in.	mm.	in.	mm.		in.	mm.		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
11R22.5	G	77081	28	75	19.4	493	41.8	1062	11.2	284	8.25, 7.50	12.5	318	497	6175	105	2800	720	5840	105	2650	720
11R22.5	H	98035	28	75	19.4	493	41.8	1062	11.2	284	8.25, 7.50	12.5	318	497	6610	120	3000	830	6005	120	2725	830
275/80R22.5	G	90375	28	75	18.9	480	40.6	1032	10.9	277	8.25, 7.50	12.2	311	511	6175	110	2800	760	5675	110	2575	760
11R24.5	G	52321	28	75	20.5	521	43.9	1116	11.0	279	8.25, 7.50	12.5	318	472	6610	105	3000	720	6005	105	2725	720
11R24.5	H	89861	28	75	20.5	521	43.9	1116	11.0	279	8.25, 7.50	12.5	318	472	7160	120	3250	830	6610	120	3000	830
275/80R24.5	G	55617	28	75	19.5	495	41.9	1064	10.6	269	8.25, 7.50	12.2	311	500	6175	110	2800	760	5675	110	2575	760

Note: Wheel listed first is the measuring wheel.

(1) Exceeding the lawful speed limit is neither recommended nor endorsed.

(2) Tire section widths and overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

(3) 5 Year / 2-Retread Limited Casing Guarantee when retreaded by an authorized Michelin Retread Technologies (MRT) Dealer or an Oliver Retread dealer.

BFGoodrich tires are subject to a continuous development program. BFGoodrich reserves the right to change product specifications at any time without notice or obligation.

MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect current Load and inflation information. Please visit our website for the latest product information. The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions. Never exceed a wheel manufacturer's limits permission from the component manufacturer.

» Take control today! In the US: bfgoodrichtrucktires.com
In Canada: www.bfgoodrich.ca

To Find Your Nearest BFGoodrich Commercial Truck Tire Dealer Call:
United States, 1-877-788-8899; Canada, 1-888-871-6666

Michelin North America, Inc. | 1 Parkway S | Greenville, SC 29615
Michelin North America (Canada), Inc. | 1001, De Maisonneuve Boulevard West, 10th Floor | Montreal, QC H3A 3C8
© 2026 MNA, Inc. All rights reserved. (06/26) | © 2026 MNA(C) All rights reserved. (06/26)

