

BFGoodrich ST244

Take control of the miles ahead with this long-lasting, even-wearing steer/all-position highway tire that's SmartWay® verified.



GOES THE DISTANCE

» Seriously long-lasting tire



MAX FUEL EFFICIENCY

» Less stops at the pump



RETREADABILITY COMES STANDARD

» Multiple lives

5 YEAR ⁽³⁾

5 Year / 2-Retread Manufacturer's Limited Casing Guarantee

Application	Highway	Regional	Urban	Coach/Bus	On/Off-Road
	Recommended Application	Acceptable Application	Acceptable Application	Acceptable Application	Acceptable Application
Position	Steer	Drive	Trailer		
	Recommended Application	Acceptable Application	Acceptable Application		

Size	Load Range	Catalog Number	Tread Depth 32nds	Max. Speed (1)		Loaded Radius		Overall Diameter		Overall Width (2)		Approved Wheels (Measuring wheel listed first)	Min. Dual Spacing (2)		Revs Per Mile	Max. Load Per Tire Single				Max. Load Per Tire Dual			
				mph	kph	in.	mm.	in.	mm.	in.	mm.		in.	mm.		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
11R22.5	G	40525	18	75	120	19.1	486	41.1	1043	10.5	267	8.25, 7.50	12.5	318	505	6175	105	2800	720	5840	105	2650	720
11R22.5	H	92401	18	75	120	19.2	487	41.1	1044	12.2	309	8.25, 7.50	12.5	318	505	6610	120	3000	830	6005	120	2725	830
275/80R22.5	G	61456	18	75	120	18.6	472	40.0	1016	10.9	277	8.25, 7.50	12.2	311	519	6175	110	2800	760	5675	110	2575	760
11R24.5	H	58109	18	75	120	20.2	513	43.3	1100	11.0	279	8.25, 7.50	12.5	318	478	7160	120	3250	830	6610	120	3000	830
275/80R24.5	G	77897	18	75	120	19.2	488	41.3	1049	10.6	269	8.25, 7.50	12.2	311	502	6175	110	2800	760	5675	110	2575	760

Note: Wheel listed first is the measuring wheel.

(1) Exceeding the lawful speed limit is neither recommended nor endorsed.

(2) Tire section widths and overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

(3) 5 Year / 2-Retread Limited Casing Guarantee when retreaded by an authorized Michelin Retread Technologies (MRT) Dealer or an Oliver Retread dealer.

BFGoodrich tires are subject to a continuous development program. BFGoodrich reserves the right to change product specifications at any time without notice or obligation.

MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect current Load and inflation information.

Please visit our website for the latest product information. The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions.

Never exceed a wheel manufacturer's limits permission from the component manufacturer.

» Take control today! In the US: bfgoodrichtrucktires.com
In Canada: www.bfgoodrich.ca

To Find Your Nearest BFGoodrich Commercial Truck Tire Dealer Call:
United States, 1-877-788-8899; Canada, 1-888-871-6666

Michelin North America, Inc. | 1 Parkway S | Greenville, SC 29615
Michelin North America (Canada), Inc. | 1001, De Maisonneuve Boulevard West, 10th Floor | Montreal, QC H3A 3C8
© 2026 MNA, Inc. All rights reserved. (06/26) | © 2026 MNA(C) All rights reserved. (06/26)

