

BFGoodrich Route Control S 19.5"

Take control in navigating the urban environment and regional roads with confidence. The new BFGoodrich Route Control S takes on all season conditions with its M+S characteristics and provides smooth wear through its micro sipes along groove edges. Resilient sidewall/shoulder helps resist shocks and impacts from curbing.




CONQUERS THE CURBS

- Bump and bruise resistant



FIGHTS IRREGULAR WEAR

- Smooth, even-wearing tread



RETREADABILITY COMES STANDARD

- Multiple lives

5 YEAR ⁽¹⁾

5 Year / 2-Retread Manufacturer's Limited Casing Guarantee

Application	Highway	Regional	Urban	Coach/Bus	On/Off-Road
Position	Steer	Drive	Trailer		
■ Recommended Application ■ Acceptable Application					

Size	Load Range	Catalog Number	Tread Depth 32nds	Max. Speed (2)		Loaded Radius		Overall Diameter		Overall Width (3)		Approved Wheels (Measuring wheel listed first)	Min. Dual Spacing (3)		Revs Per Mile	Max. Load Per Tire Single				Max. Load Per Tire Dual			
				mph	km/h	in.	mm.	in.	mm.	in.	mm.		in.	mm.		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
225/70R19.5	G	21717	15	87	140	15.1	383	32.2	817	8.8	224	6.75, 6.00	10.0	254	643	3970	110	1800	760	3750	110	1700	760
245/70R19.5	H	69107	16	75	120	15.5	393	35.3	847	9.6	244	7.50, 6.75	10.9	276	623	4940	120	2240	825	4675	120	2120	825

Note: Wheel listed first is the measuring wheel.

(1) 5 Year / 2-Retread Limited Casing Guarantee when retreaded by an authorized Michelin Retread Technologies (MRT) Dealer or an Oliver Retread dealer. See www.bfgoodrichtrucktires.com for more information.

(2) Exceeding the lawful speed limit is neither recommended nor endorsed.

(3) Tire section widths and overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

BFGoodrich tires are subject to a continuous development program. BFGoodrich reserves the right to change product specifications at any time without notice or obligation.

MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect current Load and inflation information. Please visit our website for the latest product information. The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions. Never exceed a wheel manufacturer's limits permission from the component manufacturer.

» Take control today!

In the US: bfgoodrichtrucktires.com

In Canada: <https://www.bfgoodrich.ca>

To Find Your Nearest BFGoodrich Commercial Truck Tire Dealer

Call: United States, 1-877-788-8899; Canada, 1-888-871-6666