

# MICHELIN X WORKS

## TUBELESS TYRE FOR MULTI USAGE, BUILDING SITES, TRACKS AND ROADS



- ✓ LOWER COST PER KILOMETER
- ✓ THE ROBUST TYRE WITH UP TO 35%\* MORE AGGRESSION RESISTANCE
- ✓ INCREASED LOAD CAPACITY



\* compared to 12.00 R24 XZY



# MICHELIN X WORKS

## TUBELESS TYRE FOR MULTI USAGE, BUILDING SITES, TRACKS AND ROADS



### X WORKS XZ<sup>▲</sup> 325/95 R24 (=12.00 R24) ALL POSITION

**MORE ROBUSTNESS:** Up to 35%\* aggression resistance thanks to :


- additional full protector ply **(A)**, larger tread, more resistant components and greater thickness of internal rubber.
- reinforced casing protection which provides up to 20% retreadability.

**MORE MILEAGE:** Up to +15%\* more mileage thanks to :

- a new tread width **(B)** with a greater tread depth.
- more regular wear thanks to more even distribution of ground pressure across the tread.

#### MORE TRACTION

- more edges in the contact area **(C)**
- carrying the same load with lower tyre pressure (from - 0.5 bar to - 0.8 bar compared to the standard recommended for XZY).



More edges

### X WORKS XD<sup>▲</sup> 325/95 R24 (=12.00 R24) DRIVE POSITION

#### MORE ROBUSTNESS

- more aggression resistance on crown area.

#### MORE MILEAGE

- up to 10% more mileage on tracks or on road, compared to 12.00 R24 XDY in the same condition.

#### MORE TRACTION

- massive sculpture similar to earth mover tyre technology, higher tread depth 22 mm. (+2 mm. compared to XDY).



### INCREASED LOAD CAPACITY New load index : 162/160K

#### Possible axle load at 8.5 bar


- 9,500 kgs. on single fitment
- 18,000 kgs. on twin fitment

**Single axle  
+1,500 kgs**

**Twin axle  
+3,400 kgs**

**Gross Vehicle Weight (GVW) = 45,500 kg**

Additional full protector ply



### TECHNICAL DATA

\* compared to 12.00 R24 XZY ▲ May be used with tube

Size	Load Index/ Speed Symbol	PR	Load/Tyre S/D (kg)	Max Speed (Km/hr)	Max Inflation Pressure		Overall Diameter (mm)	Section Width (mm)	Recommended Rim Width (inch)	Tube	Flap
					bar	psi					
325/95 R24 (12.00 R24)	162/160K	16	4750/4500	110	8.50	125	1223	311	8.50	24Q	24/25x8.50



Warning: Serious or fatal injury may result from tyre failure due to incorrect selection, fitting, usage or maintenance of tyres. To ensure correct selection, fitment, usage and maintenance, refer to the Michelin Truck and Bus Tyre Service Manual (Asia Pacific Edition) - available at a Michelin tyre dealer. Please consult tyre professionals for all tyre related issues.